










"ALL-STAINLESS" INDUSTRIAL PRESSURE GAUGES, TYPE PBX

TYPE PBX, with bourdon tube

STANDARD MODEL

CASE	: bayonet lock, AISI304/1.4301, IP-65	RANGE	: from -1/0 and 0-0,6 - 60 bar, acc. to EN 837-1 (see page 42)
WETTED PARTS	: AISI316Ti/1.4571		for higher pressure ranges (max. 1600 bar): see page 42
WINDOW	: mineral glass 4 mm	ACCURACY	: case Ø 63 and Ø 80 mm ±1.6% F.S. / class 1.6
DIAL	: aluminium, black figures on white		case Ø 100, Ø 160 and Ø 250 mm ±1.0% F.S. / class 1.0
POINTER	: aluminium, black	MOVEMENT	: stainless steel AISI304/1.4301
CONNECTION	: Ø63 and Ø80 mm: ¼"BSP or ¼"NPT Ø100, Ø160 and Ø250 mm: ½"BSP or ½"NPT	OPTIONS	: see page 30-31, electrical contacts and transmitters e.g.: 4-20 mA, 0-20 mA, 0-10Vdc see page 46-49

TYPE	MODEL	CASE DIAMETER (Ø in mm)				
		63	80	100	160	250
A		PBX063XA	PBX080XA	PBX100XA	PBX160XA	PBX250XA
B		PBX063XB	PBX080XB	PBX100XB	PBX160XB	PBX250XB
C		PBX063XC	PBX080XC	PBX100XC	PBX160XC	PBX250XC
D		PBX063XD	PBX080XD	PBX100XD	PBX160XD	PBX250XD
E		PBX063XE	PBX080XE	PBX100XE	PBX160XE	PBX250XE
F		PBX063XF	PBX080XF	PBX100XF	PBX160XF	PBX250XF
G		PBX063XG	PBX080XG	PBX100XG	PBX160XG	PBX250XG
H		PBX063XH	PBX080XH	PBX100XH	PBX160XH	PBX250XH
J		PBX063XJ	PBX080XJ	PBX100XJ	PBX160XJ	PBX250XJ
OPTION		EXTRA COSTS				
Lx	LIQUID FILLED CASE: GLYCERINE (in combination with electrical device: OIL see page 49)	PBX063Lx	PBX080Lx	PBX100Lx	PBX160Lx	PBX250Lx
Lx	SILICONE OIL FILLING (in combination with electrical device: OIL see page 49)	PBX063Lx	PBX080Lx	PBX100Lx	PBX160Lx	PBX250Lx